


# 가스렌지 / 콘벡션오븐 (Gas Range With Convection Oven)



품 번		수 량	
품 명	가스 렌지 / 하부 콘벡션 오븐		
모 델	<b>V6B36C</b>		
규 격	가로 914mm x 세로 933mm x 높이 914mm		
능 력	상부 6 오픈 버너		
제 조 사	VULCAN-HART COMPANY (Made in : U.S.A)		
선적중량	329 Kg (730 LBS)		
<b>에 너 지 제 원</b>			
가 스	32A	LPG or LNG	발열량 57,960 Kcal
전 기	1P 115V 60Hz 4 Amps (Blower Motor)		

## 용 도

개방형의 상부 오픈 버너에 조리용 주방기구를 이용한 조리를 합니다.

하부의 오븐은 구이류의 모든 조리과 제과 제빵용도의 오븐으로 사용이 됩니다.

주의 : 1) 파이롯트 버너의 불이 항상 켜져 있는지 확인하시기 바랍니다, 일과 중에는 항상 켜져 있어야 합니다.

2) 조리 작업 완료 후에는 중간 밸브 및 메인 밸브를 잠가 주어야 합니다.

## 제 품 사 양



- ☞ 전면, 상판 정면, 버너 박스, 측면 스텐레스로 제작
- ☞ 몸체 외부, 하부 및 상부후면 뿔 스텐레스로 제작
- ☞ 32A 상부 좌측 또는 우측 가스 연결 (후면 연결 가능)
- ☞ 8,317 Kcal/hr.(1개) 발열량의 오픈 상판 버너
- ☞ 8,064 Kcal/hr. 발열량의 콘벡션 오븐 버너
- ☞ 법랑 도색의 오븐 내부
- ☞ 각각의 파이롯트 버너를 이용한 점화 방식의 오픈 버너
- ☞ 내열에 강하고 견고한 주물 삼발이
- ☞ 100mm 높이의 오븐 배기구 기능을 겸한 스텐레스 뿔
- ☞ 152mm 높낮이 조절식 스텐레스 다리
- ☞ 분리식의 일체형 오븐 선반 레일
- ☞ 콘벡션 오븐 전기 사양 : 1P 115V 60Hz 4 Amps
- ☞ 오븐 내부 규격 685mm x 685mm x 330mm
- ☞ 65°C~287°C 온도 조절 기능의 표준 오븐
- ☞ 79°C~287°C 온도 조절 기능의 콘벡션 오븐
- ☞ 3개의 오븐랙 삽입 가능
- ☞ 표준 오븐-1개 랙 / 콘벡션 오븐-2개 랙 제공


- ☞ Stainless steel front, front top ledge, burner box, side
- ☞ Stainless steel base, exterior bottom and stub back
- ☞ 1.25"(32A) diameter front gas manifold with 1.25" rear
- ☞ 33,000 BTU/hr. open top burners with lift off headr
- ☞ 32,000 BTU/hr. convection oven burner
- ☞ porcelain oven cavity
- ☞ Individual pilots and controls for each burner
- ☞ Heavy-duty cast grates
- ☞ 4" stainless steel stub back
- ☞ 6" adjustable stainless steel legs
- ☞ Pull-out cindiment rails
- ☞ Convection oven electric : 1P 115V 60Hz 4 Amps
- ☞ Oven measures 27"w x 27"d x 13"h
- ☞ 150°F~550°F standard oven thermostat adjusts
- ☞ 175°F~550°F convection oven thermostat adjusts
- ☞ Tree rack postions
- ☞ Standard oven 1-rack / Convection 2-Racks Supplied


제품인증



비 고





**HEAVY DUTY COOKING****VULCAN****V SERIES HEAVY DUTY GAS RANGE  
36" WIDE, 6-BURNER****Model V6B36S****SPECIFICATIONS**

36" wide heavy duty gas range, Vulcan Model No. V6B36 (modular) and V6B36B (cabinet base) or V6B36S (standard oven base) and V6B36C (convection oven base). Modular construction for ease of installation. Stainless steel front, sides, plate ledge, front top ledge with pull-out condiment rails, stub back, and 6" adjustable legs on all "B", "S", & "C" models. Stainless steel extra deep crumb tray. Six 33,000 BTU/hr. cast burners with lift-off burner heads. Individual pilots and controls for each burner. Heavy duty cast burner grates, easy lift-off 11" x 12" in front, 14" x 12" in rear. Grates are separate from aeration bowl for ease of cleaning. Standard oven: 50,000 BTU/hr. with porcelain oven bottom, sides and indoor panel. Convection Oven: 32,000 BTU/hr. with porcelain oven bottom, sides and interior door panel (115v-1 phase blower motor, 4 amps, 6' cord and plug). Oven measures 27" w x 27" d x 13" h. Standard oven thermostat adjusts from 150°F - 550°F. Convection oven adjusts from 175°F - 550°F and the optional finishing oven for standard ovens adjusts from 300°F - 650°F. Standard oven supplied with one rack, convection oven with two racks. Both ovens allow for three rack positions. Oven door is heavy duty with counter weight door hinges. 1/4" diameter front gas manifold and 1/4" rear gas connection, capped. Total input 198,000 BTU/hr.

**Exterior Dimensions:**

36 3/4" d x 36" w x 36" h on 6" adjustable legs

- V6B36** 6-Burner / Modular
- V6B36B** 6-Burner / Cabinet Base
- V6B36S** 6-Burner / Standard Oven
- V6B36C** 6-Burner / Convection Oven

**STANDARD FEATURES**

- Stainless steel front, front top ledge, burner box, sides, base, exterior bottom and stub back
- 1/4" diameter front gas manifold with 1/4" rear gas connection (capped)
- 33,000 BTU/hr. open top burners with lift off heads
- 50,000 BTU/hr. standard oven burner
- 32,000 BTU/hr. convection oven burner
- Porcelain oven cavity
- Individual pilots and controls for each burner
- Heavy-duty cast grates
- 4" stainless steel stub riser
- 6" adjustable stainless steel legs for "S", "C", and "B" units (no legs for modular unit)
- Stainless steel cabinet base door
- Universal rack guides, one removable shelf (cabinet base)
- One year limited parts and labor warranty

**OPTIONAL FEATURES (Factory Installed)**

- 1/4" rear gas connection
- Cap and cover front manifold
- Stainless steel oven cavity
- 650°F oven thermostat and steel hearth ("S" models)
- Fan cooling package ("C" models)
- 4" adjustable flanged feet for modular units
- 6" adjustable flanged feet for "S", "C", and "B" units
- Less legs for dolly mounting for "S", "C", and "B" units
- Set of 4 casters, 6" high (two locking)
- 3" high toe base for curb mounting
- 3/4", 1", or 1 1/4" gas pressure regulator (specify gas type – pack loose)
- Common condiment type, telescoping plate rails

**ACCESSORIES (Packaged & Sold Separately)**

- Extra removable shelves for use with Universal rack guides (for cabinet base)
- "S" Grates
- Banking strip
- Common condiment type, telescoping plate rails (starting at 24" length)
- 10", 22", or 34" high back risers (no shelf)
- 22" single deck solid or flo-thru high shelf risers
- 34" double deck solid or flo-thru high shelf risers
- Dolly frames
- Flexible gas hose - quick disconnect & restraining device

**VULCAN**

a division of ITW Food Equipment Group LLC

P.O. Box 696 ■ Louisville, KY 40201 ■ Toll-free: 1-800-814-2028 ■ Local: 502-778-2791 ■ Quote &amp; Order Fax: 1-800-444-0602



**V SERIES HEAVY DUTY GAS RANGE**  
36" WIDE, 6-BURNER

**INSTALLATION INSTRUCTIONS**


1. A properly sized gas pressure regulator suitable for battery or single unit application must be furnished and installed. Natural gas 6.0" W.C., propane gas 10 W.C.
2. An adequate ventilation system is required for commercial cooking equipment. Information may be obtained by writing to the National Fire Protection Association, 1 Batterymarch Park, Quincy, MA 02269, www.NFPA.org. When writing, refer to NFPA No. 96.
3. These units are manufactured for installation in accordance with ANSZ223.1A (latest edition), National Fuel Gas Code. Copies may be obtained from The American Gas Association, 400 N Capitol St. NW, Washington, DC 20001, www.AGA.org.

4. Clearances	Rear	Sides
Combustible	10"	10"
Non-combustible	0"	0"

5. For proper combustion, install equipment on adjustable legs or casters. On curb or platform, allow 3½" front overhand. Toe base with leveling bolts are required for curb installation. Specify when ordering.
6. Cannot be battered with GH series equipment.
7. This appliance is manufactured for commercial installation only and is not intended for home use.

**NOTE:** In line with its policy to continually improve its product, Vulcan reserves the right to change materials and specifications without notice.

Specify type of gas when ordering.  
Specify altitude when above 2,000 feet.



TOP CONFIGURATION	MODEL NUMBER	DESCRIPTION	TOTAL INPUT BTU / HR	SHIPPING WEIGHT LBS / KG
	<b>V6B36</b>	6-Burner / Modular	198,000	400 / 180
	<b>V6B36B</b>	6-Burner / Cabinet Base	198,000	435 / 196
	<b>V6B36S</b>	6-Burner / Standard Oven Base	248,000	690 / 311
	<b>V6B36C</b>	6-Burner / Convection Oven Base	230,000	730 / 329

This appliance is manufactured for commercial use only and is not intended for home use.



a division of ITW Food Equipment Group LLC

P.O. Box 696 ■ Louisville, KY 40201 ■ Toll-free: 1-800-814-2028 ■ Local: 502-778-2791 ■ Quote & Order Fax: 1-800-444-0602

**NOTE:** In line with its policy to continually improve its products, Vulcan reserves the right to change materials and specifications without notice.